



Trees




What is a Tree

- ❑ In computer science, a tree is an abstract model of a hierarchical structure
- ❑ A tree consists of nodes with a parent-child relation
- ❑ Applications:
 - Organization charts
 - File systems
 - Programming environments



Tree Terminology

- ❑ Root: node without parent (A)
- ❑ Internal node: node with at least one child (A, B, C, F)
- ❑ External node (a.k.a. leaf): node without children (E, I, J, K, G, H, D)
- ❑ Ancestors of a node: parent, grandparent, grand-grandparent, etc.
- ❑ Depth of a node: number of ancestors
- ❑ Height of a tree: maximum depth of any node (3)
- ❑ Descendant of a node: child, grandchild, grand-grandchild, etc.
- ❑ Subtree: tree consisting of a node and its descendants




Tree ADT

- We use positions to abstract nodes
 - Generic methods:
 - integer `size()`
 - boolean `empty()`
 - Accessor methods:
 - position `root()`
 - list<position> `positions()`
 - Position-based methods:
 - position `p.parent()`
 - list<position> `p.children()`
- ◆ Query methods:
 - boolean `p.isRoot()`
 - boolean `p.isExternal()`
 - ◆ Additional update methods may be defined by data structures implementing the Tree ADT

Preorder Traversal

- ❑ A traversal visits the nodes of a tree in a systematic manner
- ❑ In a preorder traversal, a node is visited before its descendants
- ❑ Application: print a structured document


Algorithm *preOrder(v)*
visit(v)
for each child *w* of *v*
preorder(w)



Postorder Traversal

- In a postorder traversal, a node is visited after its descendants
- Application: compute space used by files in a directory and its subdirectories


Algorithm *postOrder(v)*
for each child *w* of *v*
 postOrder(w)
visit(*v*)



Binary Trees


- A binary tree is a tree with the following properties:
 - Each internal node has at most two children (exactly two for **proper** binary trees)
 - The children of a node are an ordered pair
- We call the children of an internal node **left child** and **right child**
- Alternative recursive definition: a binary tree is either
 - a tree consisting of a single node, or
 - a tree whose root has an ordered pair of children, each of which is a binary tree

- Applications:
 - arithmetic expressions
 - decision processes
 - searching




Arithmetic Expression Tree

- Binary tree associated with an arithmetic expression
 - internal nodes: operators
 - external nodes: operands
- Example: arithmetic expression tree for the expression $(2 \times (a - 1) + (3 \times b))$



Decision Tree

- Binary tree associated with a decision process
 - internal nodes: questions with yes/no answer
 - external nodes: decisions
- Example: dining decision



Properties of Proper Binary Trees


□ Notation

n number of nodes

e number of
external nodes

i number of internal
nodes

h height



◆ Properties:

■ $e = i + 1$

■ $n = 2e - 1$


■ $h \leq i$

■ $h \leq (n - 1)/2$

■ $e \leq 2^h$

■ $h \geq \log_2 e$

■ $h \geq \log_2 (n + 1) - 1$




BinaryTree ADT

- The BinaryTree ADT extends the Tree ADT, i.e., it inherits all the methods of the Tree ADT
- Additional methods:
 - position p.left()
 - position p.right()
- Update methods may be defined by data structures implementing the BinaryTree ADT
- **Proper binary tree:** Each node has either 0 or 2 children

Inorder Traversal


- In an inorder traversal a node is visited after its left subtree and before its right subtree
- Application: draw a binary tree
 - $x(v)$ = inorder rank of v
 - $y(v)$ = depth of v

```
Algorithm inOrder( $v$ )  
  if  $\neg v.isExternal()$   
    inOrder( $v.left()$ )  
  visit( $v$ )  
  if  $\neg v.isExternal()$   
    inOrder( $v.right()$ )
```



Print Arithmetic Expressions

- Specialization of an inorder traversal
 - print operand or operator when visiting node
 - print "(" before traversing left subtree
 - print ")" after traversing right subtree



Algorithm *printExpression(v)*

```
if ¬v.isExternal()
    print("(")
    inOrder(v.left())
    print(v.element())
if ¬v.isExternal()
    inOrder(v.right())
    print(")")
```

$((2 \times (a - 1)) + (3 \times b))$

Evaluate Arithmetic Expressions

- Specialization of a postorder traversal
 - recursive method returning the value of a subtree
 - when visiting an internal node, combine the values of the subtrees

Algorithm *evalExpr(v)*

if *v.isExternal()*

return *v.element()*


else

x ← *evalExpr(v.left())*

y ← *evalExpr(v.right())*


◇ ← operator stored at *v*

return *x* ◇ *y*





Euler Tour Traversal

- ❑ Generic traversal of a binary tree
- ❑ Includes a special cases the preorder, postorder and inorder traversals
- ❑ Walk around the tree and visit each node three times:
 - on the left (preorder)
 - from below (inorder)
 - on the right (postorder)





Linked Structure for Trees

- A node is represented by an object storing
 - Element
 - Parent node
 - Sequence of children nodes
- Node objects implement the Position ADT




Linked Structure for Binary Trees

- A node is represented by an object storing
 - Element
 - Parent node
 - Left child node
 - Right child node
- Node objects implement the Position ADT



Array-Based Representation of Binary Trees

- Nodes are stored in an array A



- Node v is stored at $A[\text{rank}(v)]$
 - $\text{rank}(\text{root}) = 1$
 - if node is the left child of $\text{parent}(\text{node})$,
 $\text{rank}(\text{node}) = 2 \cdot \text{rank}(\text{parent}(\text{node}))$
 - if node is the right child of $\text{parent}(\text{node})$,
 $\text{rank}(\text{node}) = 2 \cdot \text{rank}(\text{parent}(\text{node})) + 1$

